

Section 1. Identification

GHS product identifier:	Ready Mix Concrete	
Other means of identification:	Concrete, Colored Concrete, Freshly Mixed Concrete	
Relevant identified uses of the substance or mixture and uses advised against:	Ready Mix Concrete is used in the construction of various structures and objects.	
Supplier's details:	American Materials LLC 717 Short Street Eau Claire, WI 54701 (715) 835-2251	Emergency telephone number (24 hours): CHEMTREC: (800) 424- 9300

Section 2. Hazards Identification

GHS Classification:	CARCINOGENICITY – Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) – Category 2 SKIN CORROSION/IRRITATION – Category 1B SERIOUS EYE DAMAGE/EYE IRRITATION – Category 1 SKIN SENSITIZATION – Category 1
----------------------------	--

GHS Label elements

Hazard pictograms:



Signal word:

Danger

Hazard statements:

May cause damage to organs (lung) through prolonged or repeated exposure
Causes severe skin burns and eye damage
May cause cancer (Inhalation)
Causes serious eye irritation
May cause an allergic skin reaction

Precautionary statements:

Prevention:

Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Wash any exposed body parts thoroughly after handling. Avoid breathing dust. Contaminated clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response:

If exposed or concerned: Get medical advice/attention if irritation or rash occurs. If swallowed rinse mouth, do NOT induce vomiting. If on skin: Take off immediately all contaminated clothing. Rinse/wash skin with plenty of water/shower. Wash contaminated clothing before reuse. If in eyes: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do.

Storage:

Restrict or control access to ready mix concrete (store locked up).

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified (HNOC):

None known

Supplemental Information:

Respirable Crystalline Silica (RCS) may cause cancer. Wet, freshly mixed concrete is not expected to pose respiratory concern. Ready Mix Concrete is comprised of cement, additives and a naturally occurring mineral complex that contains varying quantities of quartz (crystalline silica). When set/cured Ready Mix Concrete is subject to various natural or mechanical forces it may produce small particles (dust) which may contain respirable crystalline silica (particles less than 10 micrometers in aerodynamic diameter). Repeated inhalation of respirable crystalline silica (quartz) may cause lung cancer according to IARC and NTP; ACGIH states that it is a suspected cause of cancer. Other forms of RCS (e.g., tridymite and cristobalite) may also be present or formed under certain Industrial processes.

Section 3. Composition/Information on Ingredients

Substance/mixture: Ready Mix Concrete

CAS number/other identifiers

Ingredient name	%	CAS Number
Aggregates (crushed stone, sand, gravel)	>35	Mixture - Varies
Portland Cement	>25	65997-15-1
Ashes	0 – 25	Mixture - Varies
Water	>5	7732-18-5
Crystalline Silica (Quartz)	<0.1	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to process variation. Portland Cement may contain trace (<0.05%) amounts of chromium salts or compounds (including hexavalent chromium) or other metals (including nickel compounds) found to be hazardous or toxic in some chemical forms. These metals are present mostly as trace substitutions within the principal minerals. Other trace constituents may include potassium and sodium sulfate compounds. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of necessary first aid measures

Eye Contact:	If exposed or concerned: get medical attention. Do not allow individual to rub eyes. Flush eyes gently under running water for 15 minutes or longer, making sure that the eyelids are held open. Other than washing with water, do not attempt to remove material from eyes. Remove contact lenses, if present and easy to do. Obtain medical attention for eye contact with wet concrete.
Inhalation:	Move exposed individual to fresh air. Dust in throat and nasal passages should clear naturally by coughing, sneezing and nasal discharge. Obtain medical attention if symptoms persist or develop later.
Skin Contact:	Wash affected areas with water and soap. Remove contaminated clothing and wash before reuse. If irritation persists or develops later, obtain medical attention.
Ingestion:	Ingestion is not a common route of occupational exposure. If swallowed and irritation or discomfort occurs, obtain medical attention.

Most important symptoms/effects, acute and delayed potential acute health effects

Eye Contact:	Exposure to dust from dry ingredients or hardened cement can cause irritation and tearing of the eyes. Exposure to wet concrete may result in irritation or burns.
Inhalation:	Symptoms of exposure may include upper respiratory discomfort with coughing and sneezing. Inhalation may cause upper respiratory tract infection. A "rare" acute form of silicosis may develop from inhalation of extremely high concentrations of crystalline silica over a period of several months to five years.
Skin contact:	Ready Mix Concrete contains Portland Cement, which may contain trace amounts of hexavalent chromium and is linked with allergic sensitization reactions in some individuals. These reactions may lead to contact dermatitis and skin ulceration. Exposure to dust from dry ingredients or hardened cement can cause skin irritation, dermatitis and/or redness to the exposed skin. Wet concrete exhibits caustic, abrasive and dehydrating properties. Irritation or pain may be delayed for several hours and cannot be relied upon as an indication of exposure.
Ingestion:	Ingestion is not a common route of occupational exposure. If swallowed and irritation or discomfort occurs, obtain medical attention.

Over-exposure signs/symptoms

Notes to physician:	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
Specific treatments:	Not Applicable
Protection of first-aiders:	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
General information:	Pre-existing medical conditions that may be aggravated by exposure include disorders of the eye, skin and lung (including asthma and other breathing disorders). If addicted to tobacco, smoking will impair the ability of the lungs to clear themselves of dust.

See toxicological information (Section 11)

Section 5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:	Not combustible. Use extinguishing agent appropriate for surrounding flammable materials.
Unsuitable extinguishing media:	None known.
Specific hazards arising from the chemical:	Not combustible. Nonflammable. Spalling of hardened concrete may occur under conditions of intense heat.
Hazardous thermal decomposition products:	Material is not combustible
Special protective actions for firefighters:	Material is nonflammable. Use appropriate procedures for surrounding flammable materials.
Special protective equipment for firefighters:	Use protective equipment appropriate for surrounding materials. No specific precautions.

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For response personnel:	Keep unprotected personnel out of the area. Do not dry sweep dusty material. All local and Federal laws governing waste disposal must be followed.
Environmental precautions:	Clean spilled material immediately. Contain spills and wash water to prevent run-off into public waterways. Remove wet concrete from roadways immediately. Do not dry sweep spilled dusty material.

Methods and materials for containment and cleaning up

Small spill:	Alkali resistant gloves, long sleeves, long pants and safety glasses should be used by clean up personnel for wet concrete releases.
Large spill:	Waterproof boots and goggles should be used. Eye protection and appropriate respirator protection should be used to protect clean up personnel against dust.

Section 7. Handling and Storage

Precautions for safe handling

Protective measures:	Use personnel protective equipment to avoid direct contact with concrete. Remove contaminated clothes as soon as possible. Dust may be generated during handling or mixing dry powder or from cutting, breaking or crushing hardened material. Use wet cutting methods when possible.
Advice on general occupational hygiene:	Observe good industrial hygiene practices. Promptly remove dusty clothing and launder before reuse.
Conditions for safe storage, including any incompatibilities:	Store away from moisture, acids, and other incompatible materials. Store and use material in such a way as to prevent release to drains or waterways.

Section 8. Exposure Controls/Personal Protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Particulates not otherwise classified (CAS SEQ250)	ACGIH TLV (United States, 3/2012)
	TWA: 3 mg/m ³ . Form: Respirable particles
	TWA: 10 mg/m ³ . Form: Inhalable particles
	OSHA PEL (United States, 2/2013)
	PEL: 5 mg/m ³ . Form: Respirable fraction
	PEL: 15 mg/m ³ . Form: Total dust
Portland Cement	TWA: 5 mg/m ³ . Form: Respirable fraction
	TWA: 15 mg/m ³ . Form: Total dust
	ACGIH TLV (United States, 3/2012)
	TWA: 3 mg/m ³ . Form: Respirable particles
TWA: 10 mg/m ³ . Form: Total dust	
OSHA PEL (United States, 6/2010)	

PEL: 5 mg/m³. Form: Respirable dust

PEL: 15 mg/m³. Form: Total dust

Crystalline Silica (Quartz) (CAS 14808-60-7)

ACGIH TLV (United States, 3/2012)

TWA: 0.025 mg/m³. Form: Respirable dust

OSHA PEL (United States, 6/2010)

TWA: 10 mg/m³. Form: Respirable dust

TWA: 30 mg/m³. Form: Total dust

Appropriate engineering controls:	The use of ventilation or other engineering controls may be necessary to maintain airborne levels below any applicable limits. Under normal operations general ventilation should suffice.
Environmental exposure controls:	Use general ventilation, local exhaust and /or wet suppression methods to maintain exposures below allowable exposure limits.
Exposure guidelines:	OSHA PELs, MSHA PEL, and ACGIH TLVs are 8-hr TWA values. NIOSH RELs are for TWA exposures up to 10-hr/day and 40-hr/wk. Occupational exposure to a nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Terms including “Particulates Not Otherwise Classified,” “Particulates Not Otherwise Regulated,” “Particulates Not Otherwise Specified,” and Inert or Nuisance Due” are often used interchangeably; however, the user should review each agency’s terminology for difference in meanings.

Individual protection measures

Hygiene measures:	Use good personal hygiene practices. Do not consume or store food in the work area. Wash hands thoroughly before eating, drinking, or smoking.
Eye/face protection:	Safety glasses with side shields should be worn as minimum protection from dust. Dust goggles or full face protection should be worn when very dusty conditions are present or are anticipated.

Skin protection

Hand protection:	Use alkali resistant gloves to provide hand protection from concrete.
Body protection:	Clothing with long sleeves will provide protection. Waterproof boots high enough to prevent cement from entering should be worn when workers will be standing in wet concrete. Contaminated work clothing should be washed after use.
Other skin protection:	Clothing with long sleeves and long pants should be used to prevent contact with wet concrete.
Respiratory protection:	The need for respiratory protection should be evaluated by a qualified professional. The use of respirators for controlling exposures in excess of the PEL must comply with OSHA and MSHA requirements for medical surveillance, respiratory fit testing, repair and cleaning, and user training. In dusty areas, air monitoring for dust and quartz should be conducted regularly. Dust and quartz levels in excess of appropriate exposure limits should be reduced by all feasible engineering controls, including but not limited to, wet suppression, ventilation, process enclosure, and enclosed employee work stations.

Section 9. Physical and Chemical Properties

Appearance

Physical State:	Flowable, granular mud-like material	Lower and upper explosive flammable limits:	No test data available
Color:	Gray	Vapor pressure:	No test data available
Odor:	None	Vapor density:	Not applicable
Odor threshold:	Not applicable	Relative density:	1.5 – 3.0
pH:	12-13 in water	Solubility:	Not applicable
Melting point:	Not applicable	Solubility in water:	Negligible
Boiling point:	Not applicable	Partition coefficient:	
		n-octanol/water:	Not applicable
Flash point:	Not applicable	Auto-ignition temperature	No test data available
Burning time:	Not applicable	Decomposition temperature	No test data available
Burning rate:	Not applicable	SADT:	Not applicable
Evaporation rate:	Not applicable	Viscosity:	Not applicable
Flammability (solid, gas):	No		

Section 10. Stability and Reactivity

Reactivity:	Stable
Chemical Stability:	This material is considered stable under recommended handling and storage conditions.
Possibility of hazardous reactions:	Polymerization will not occur.
Conditions to avoid:	Keep dry until used. Avoid contact with incompatible compounds.
Incompatible materials:	Wet cement may react with acids, aluminum, ammonium salts, alkali and alkaline earth compounds.

Section 11. Toxicological Information

Information on toxicological effects

Acute toxicity:	Not reported to be acutely toxic.
Irritation/Corrosion:	Skin: May cause skin burns or skin ulcers. Eyes: May cause eye irritation or serious eye damage. Respiratory: Studies indicate an increased risk of lung cancer from chronic exposure to respirable crystalline silica. This effect was more pronounced in those with silicosis. Studies have also linked crystalline silica exposure with autoimmune diseases and kidney disorders.
Sensitization:	May cause sensitization due to the potential presence of trace amounts of hexavalent chromium.
Mutagenicity:	No data available to indicate product or any components present at a greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity:	See chart below.

Product/Ingredient name	OSHA	IARC	ACGIH	NTP
Portland Cement	-	-	A4	-

Crystalline Silica (Quartz) CAS 14808-60-7	-	1	A2	Know to be a human carcinogen
---	---	---	----	-------------------------------

Reproductive toxicity: Not expected to be a reproductive hazard.

Teratogenicity: Not expected to be a teratogenic hazard.

Specific target organ toxicity (single exposure)

Name	Category	Route of Exposure	Target Organs
Crystalline Silica (Quartz) CAS 14808-60-7	-	Inhalation	Not reported to have effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of Exposure	Target Organs
Crystalline Silica (Quartz) CAS 14808-60-7	-	Inhalation	May cause damage to organs (lung) through prolonged or repeated exposure.

Potential chronic health effects: General: Prolonged inhalation of respirable crystalline silica may be harmful. May cause damage to organs (lungs) through prolonged or repeated exposure. There are reports in the literature suggesting that excessive crystalline silica exposure may be associated with autoimmune disorders and other adverse health effects involving the kidney. In particular, the incidence of scleroderma (thickening of the skin caused by swelling and the thickening of fibrous tissue) appears to be higher in silicotic individuals. To date, the evidence does not conclusively determine a causal relationship between silica exposure and these adverse health effects.

Aspiration hazard: Due to the physical form of the product it is not an aspiration hazard.

Section 12. Ecological Information

Persistence and degradability: No available data.
 Bioaccumulative potential: No available data.
 Mobility in soil: No available data.
 Other adverse effects: No known significant effects or critical hazards.

Section 13. Disposal Considerations

Disposal Methods: Dispose of waste product and unused product in compliance with federal, state and local requirements. Used material which has become contaminated, may have significantly different characteristics based on the contaminant and should be evaluated accordingly. The product may be contaminated during use and it is the responsibility of the user to assess the appropriate disposal method in that situation.

Section 14. Transportation Information

	DOT Classification	IMDG	IATA
UN number	Not regulated	Not regulated	Not regulated
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing Group	-	-	-
Environmental hazards	-	-	-
Additional Information	-	-	-

Special precautions for user:

It is the responsibility of the transporting entity to follow all applicable laws, regulations, and rules regarding the transport of this material.

Section 15. Regulatory Information

U.S. Federal regulations:

OSHA Hazard Communication Standard, 29 CFR 1910.1200	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200
TSCA Section 12(b) Export Notification (40 CFR 707, Subpart. D):	Not regulated
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):	Not listed
CERCLA Hazardous Substance List (40 CFR 302.4):	Not listed
Clean Air Act Section 112 (b): Hazardous Air Pollutants (HAPs):	Not regulated
Clean Air Act Section 112[®] Accidental Release Prevention (40 CFR 68.130):	Not regulated
Safe Drinking Water Act (SDWA):	Not regulated

SARA 311/312

Composition/information on ingredients

Name	%	Fire Hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Crystalline Silica (Quartz)	>1	No	No	No	No	Yes

SARA 313

	Product Name	CAS Number	%
Form R-Reporting requirements	Crystalline Silica (Quartz)	14808-60-7	Not Regulated

State Regulations

Massachusetts RTK:	Listed
New Jersey RTK:	Listed
Pennsylvania RTK:	Listed
Rhode Island RTK:	Listed

California Prop. 65

WARNING: This product contains crystalline silica and chemicals (trace metals) known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Crystalline Silica (Quartz) CAS 14808-60-7	Yes	No	No	No

International Regulations

Ingredient name	CAS #	TSCA	Canada	WHMIS	EEC
Portland Cement	65997-15-1	Yes	DSL	D2A	EINECS
Water	7732-18-5	Yes	DSL	-	EINECS
Crystalline Silica (Quartz)	14808-60-7	Yes	DSL	-	EINECS

WHMIS Classification

D2A "Materials Causing Other Toxic Effects"

Section 16. Other Information

Date of issue: 06/17/2020

Version: 06/017/2020

Revised Section(s):

Notice to reader

Disclaimer:

The information presented above is based on our current data and considered to be accurate as of the date of preparation of this Safety Data Sheet. However, no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information. Users should perform their own investigations as to the suitability of the information for their own particular purpose. In addition, no responsibility can be assumed by American Materials LLC for any damage, injury, loss of profit, damages of any third party, direct or indirect, resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the material.